



# **PF Series**

### **Fibreglass Media Filter**

- Tank body is made from a superior grade polymer with UV resistant fibreglass
  - Suitable for all types of pool envirnments
    - Resistant to chemicals & corrosion
  - Suitable for use with all types of filtration media
  - Large "Palm-Action" handle for easy positioning of Multi-Port Valve

Wholly Australian Owned Company

www.reltech.com.au



Filtration is the key to any crystal clear swimming pool. PF Series, fibreglass media filters require little ongoing maintenance as compared to other types of filters, allowing you more time to enjoy your pool.

PF Series filters are manufactured from high grade fibreglass and polymer resins utilising the latest engineering techniques, which gives them superior strength for demanding applications and long life in our harsh Australian conditions.

PF media filter internal components have been designed to achieve a balanced and evenly distributed water flow throughout the media bed, resulting in high filtration efficiency at high flow rates. The balanced design also ensures effective backwashing with minimal water wastage.

#### PF MEDIA FILTER FEATURES

- Available in 4 common sizes 25", 28" (40mm and 50mm), 32" and 36".
- PF25 & PF28 both have an inner tank made from a strong P.E. themoplastic material with UV resistent fibreglass on the outside for extra strength. All other sizes are made with a full UV resistant, corrosion proof fiberglass tank
- Designed for high pressure, low to high flow rate applications
- Ideally suited to be used in conjunction with Reltech "PR" Premium and Ecoflo "V3" energy efficent variable 3 Speed Pumps
- Suitable for all types of pool environments
- Resistant to chemicals & corrosion
- Suitable for use with all types of media including Ecoflo Glass, sand and zeolite
- Large "Palm-Action" handle for easy positioning of Multi-Port Valve
- Quality barrel unions fitted for easy plumbing & servicing. Comes with a clear tube for backwash checking
- Supplied with quality stainless steel, oil filled pressure gauge
- 10 year limited tank warranty
- 12 month warranty on Multi-Port Valve and internal filter components

**AVAILABLE FROM** 


## MATCHING RELTECH PUMPS FOR PF SERIES MEDIA FILTERS

RELTECH PF MEDIA FILTER MODEL	RELTECH MATCHING PUMP MODELS	MPV PIPE SIZE (MM)	DESIGN FLOW RATE (L/MIN)	FILTER AREA (M²)	ECOFLO GLASS MEDIA REQ'D (KG)	SAND REQ'D (KG)
PF25	PR100 / V3	40	260	0.32	135	150
PF28-40	PR125 - PR150 / V3	40	325	0.40	150	200
PF28-50	PR150 / V3	50	336	0.41	150	200
PF32	PR150 - PR200 / V3	50	415	0.50	210	250
PF36	PR200	50	520	0.64	255	300

Maximum recommended working pressure: 250 kPa Testing pressure: 400kPa Maximum Water Temperature: 43°C

#### PF SERIES DIMENSIONS

	RELTECH PF MEDIA FILTER MODEL	TANK DIAMETER D (MM)	HEIGHT H (MM)				
	PF25	635	950				
	PF28-40	710	1020				
	PF28-50	723	1092				
	PF32	800	1200				
	PF36	900	1300				



 $\bigoplus$ 



## RELTECH RECOMMENDS ECOFLO GLASS FILTERATION MEDIA



43-45 Kylta Road West Heidelberg Victoria 3081 Australia P: + 613 9459 3838 F: + 613 9459 4038 E: office@reltech.com.au